
CR-001 - 2-conductor through terminal block

Spare Part Number: CR-001

Net Weight: 0.00kg

Net Dimensions: 0.00cm x 0.00cm x 0.00cm

Technical Datasheet: [Protected Link](#)

Description

CR-001 2-conductor through terminal block

2.5 mm²; suitable for Ex e II applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm²; gray

WAG20021201

Specifications

Ratings per IEC/EN

| Ratings per | IEC/EN 60947-7-1 |
|-------------------------------|--|
| Nominal voltage (III/3) | 800V |
| Rated impulse voltage (III/3) | 8kV |
| Rated current | 24A |
| Rated current 2 | 32A |
| Legend (ratings) | (III / 3) ? Overvoltage category III / Pollution degree 3 |

Ratings per UL

| | |
|--------------------------------|---------|
| Approvals per | UL 1059 |
| Rated voltage UL (Use Group B) | 600V |
| Rated current UL (Use Group B) | 20A |
| Rated voltage UL (Use Group C) | 600V |
| Rated current UL (Use Group C) | 20A |

Ratings per CSA

| | |
|---------------------------------|-----------------|
| Approvals per | CSA 22.2 No 158 |
| Rated voltage CSA (Use Group B) | 600V |
| Rated current CSA (Use Group B) | 20A |
| Rated voltage CSA (Use Group C) | 600V |
| Rated current CSA (Use Group C) | 20A |

Equipment Ref
830 Ref **TB6, TB7**

812 Ref **TB2-TB3-TB4**

812 Ref **TB2-TB3-TB4**

Catalogues/Families

| | |
|----------------------|--|
| Spare Part Type | |
| Electrical Component | |
| Spare Part Group | |
| Others | |
| Stock Type | |
| Made to Order | |

Product Gallery