

CC-105 - Contactor/Modular monostable relay



Product Code: CC-105

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Custom Field 1 (UPC): [Protected Link](#)

Description

CC-105 Contactor/Modular monostable relay

Ordinary relays are "monostable" type, and this relay belongs to "monostable" type. With monostable relays, the contacts automatically return to the release state when the excitation current is switched off.

Contactor 3-Pole N-O 24VDC

FIN222290244000

Basic Specs

Contact Configuration: DPST-NO

Coil Voltage:	24VDC
Contact Current:	20A
Product Range:	22 Series
Relay Mounting:	DIN Rail, Panel
Coil Type:	DC
Contact Voltage VAC:	250VAC
Relay Terminals:	Screw
Contact Voltage VDC:	30V
Contact Material:	Silver Tin Oxide
Coil Resistance:	460ohm

Equipment Ref

620 Ref. **KUVA, KUVVC, KM11, KM12**

621 Ref. **KUVA, KUVVC, KM11, KM12**

830 Ref. **KUVA, KUVVC, KM11, KM12**

810 Ref. **KCG, KF, KP, KV1, KV2** (no longer in use. see [CC-125](#))

812 Ref. **KCG, KF, KP, KV1, KV2** (no longer in use. see [CC-125](#))

Specification

Suitable for the following equipment models:	
CLASSIC 3 P	
CLASSIC 4 P	
EASY TO PLATE EVO 3 IPD	
EASY TO PLATE EVO 3	

IPI	
EASY TO PLATE EVO 4	
IPD	
EASY TO PLATE EVO 4	
IPI	
EASY TO PLATE EVO 5	
BPD	
EASY TO PLATE EVO 5	
BPI	
EASY TO PLATE EVO 5	
IPD	
EASY TO PLATE EVO 5	
IPI	
EVO 3 EDLF	
EVO 3 ELF	
EVO 3 IP	
EVO 4 E	
EVO 4 EDLF	
EVO 4 ELF	
EVO 4 IP	
EVO 5 BP	
EVO 5 E	
EVO 5 ELF	
EVO 5 IP	
Spare Part Type	
Electrical Component	
Spare Part Group	
Contactor	
Stock Type	
Standard Stock	

Product Gallery



