

# CR-001 - 2-conductor through terminal block

**Product Code:** CR-001

**Weight:** 0.00kg

**Dimensions:** 0.00cm x 0.00cm x 0.00cm

**Technical Datasheet:** [Protected Link](#)

## Description

### CR-001 2-conductor through terminal block

## Specifications

### Ratings per IEC/EN

Ratings per	IEC/EN 60947-7-1
Nominal voltage (III/3)	800V
Rated impulse voltage (III/3)	8kV
Rated current	24A
Rated current 2	32A
Legend (ratings)	(III / 3) ? Overvoltage category III / Pollution degree 3

### Ratings per UL

Approvals per	UL 1059
Rated voltage UL (Use Group B)	600V
Rated current UL (Use Group B)	20A
Rated voltage UL (Use Group C)	600V
Rated current UL (Use Group C)	20A

### Ratings per CSA

Approvals per	CSA 22.2 No 158
Rated voltage CSA (Use Group B)	600V
Rated current CSA (Use Group B)	20A
Rated voltage CSA (Use Group C)	600V
Rated current CSA (Use Group C)	20A

### Equipment Ref

830 Ref **TB6, TB7**

812 Ref **TB2-TB3-TB4**

812 Ref **TB2-TB3-TB4**

### Specification

Spare Part Type	
Electrical Component	
Spare Part Group	
Others	
Stock Type	
Made to Order	

**Product Gallery**